

# Low Voltage Monopoint Canopies


## 2" Canopy - Remodel

The 2" inch remodel canopy shares all the aesthetic features of the new construction canopy, but is designed for post construction lighting applications. Compatible with ceiling or wall thickness up to 1" for the integral version and 1.75" for the remote version. Fixture not included.



### 2" Canopy: Integral Transformer (MPT1-S-N)

- Unit features an integral wiring chamber, swing arm clamps to secure canopy.
- Canopy is powered with 60 watt integral 12 volt electronic transformer. Optional 120 or 277 volt.
- Ceiling or wall mount requires only 4.5" of clearance
- Installs in surfaces up to 1" thick
- UL listed for direct contact with insulation




**Ordering Code:** MPT1 - S - N - [ ] - [ ] - [ ]

**Code**


**Voltage**

1	2
120	277

**Trim Style**



**R**  
Round



**S**  
Square


**Metal Finish**

<b>AL</b>	<b>PN</b>	<b>RB</b>
Aluminum	Polished Nickel	Rubbed Bronze



### 2" Canopy: Remote Transformer (MPT1-S-R)


- Unit features an integral wiring chamber, swing arm clamps to secure canopy
- Ceiling or wall mount requires only 3.5" of clearance
- Installs in surfaces up to 1.75" thick
- UL listed for direct contact with insulation




**Ordering Code:** MPT1 - S - R - [ ] - [ ]

**Code**

**Trim Style**



**R**  
Round



**S**  
Square

**Metal Finish**

<b>AL</b>	<b>PN</b>	<b>RB</b>
Aluminum	Polished Nickel	Rubbed Bronze