


Rotor

Adjustable fixture with 24kt gold plated brass socket pins | Pivots 270° at the socket and rotates 360° | Open fixture rated low voltage MR16 lamp up to 50 watts (not included)



Ordering Code:

RTR - [] - [] - []

Fixture

RTR
Rotor

System

CA4	CA6	TR4	TR6	BTC	BTW	LT	NS
4" Cable	6" Cable	4" Twin Rail	6" Twin Rail	Basis Ceiling	Basis Wall (Max. 16")	Liana	No System Connector

Overall Length

ST	6" - 36"
5" Standard Length	Specify Length

Metal Finish

AL	PN	RB
Satin Aluminum	Polished Nickel	Rubbed Bronze

Compatible Accessories:


Single lens clip, single and double accessory holders, back shield, snoot, barn doors, glass lens, louver, filter. See accessory ordering guide page 213 column TSA-03.

LOW VOLTAGE FIXTURES & PENDANTS

FIGURES

Flexi-Spot

Adjustable fixture with optional glass shade | 90° pivot at the socket and rotates 360° | Open fixture rated low voltage MR16 lamp up to 50 watts (not included)



Ordering Code:

FLX - [] - [] - [] - []

Fixture

FLX
Flexi-Spot

System

CA4	CA6	TR4	TR6	BTC	BTW	LT	NS
4" Cable	6" Cable	4" Twin Rail	6" Twin Rail	Basis Ceiling	Basis Wall (Max. 16")	Liana	No System Connector

Overall Length

ST	6" - 72"
5" Standard Length	Specify Length

Diffuser Color

AM Amber	CB Cobalt	GR Green	RD Red	WH White	NG No Glass

Metal Finish

AL	PN	RB
Satin Aluminum	Polished Nickel	Rubbed Bronze

Compatible Accessories (not compatible with glass diffuser):

Single lens clip, single and double accessory holders, back shield, snoot, barn doors, glass lens, louver, filter. See accessory ordering guide page 213 column TSA-03.